

Rugged Mobile Field Controller



- MIL-STD-810G and IP68 Compliance
- Microsoft Windows Mobile®
- 1GHz Processor
- Integrated *Bluetooth*® Wireless and 3.5G Cellular Connectivity
- Sunlight Readable Display 3.5 inch
- Embedded High Sensitivity GPS Receiver
- 5MP Autofocus Camera

SPECIFICATIONS

Computer

CPU	1 GHz
OS	Microsoft Windows Mobile® 6.5
Memory	512MB NAND Flash and 8GB iNAND
Display	3.5" VGA (480 x 640 pixel)
Interface	Wireless LAN 802.11 b/g Bluetooth® (v2.0 +EDR Class 2) USB Type Mini-B

Integrated Sensor

GPS Type	SIRF Star IV™ chipset
Horizontal Accuracy (RMS) ¹	DGPS ² : 1m to 3m (3.3' to 9.9'), Point Positioning: 5m (16.4')
Built-in Camera	5MP, Autofocus Camera

Environmental

Dust/Water Protection	IP68
Operating Temperature	-22°F to 140°F (-30°C to 60°C)
MIL-STD-810G	Drop 5' (1.52m), Vibration, Humidity

Physical

Dimensions	7 x 3.5 x 1.18 in. (h x w x d) (178 x 89 x 30mm)
Weight with Battery	17.64 oz (500g)
Battery	Removable Li-ion Rechargeable Battery, 3.72V, 5600mAh
Operating Time	12 hours with Bluetooth® connection
Recharging Time	3.5 hours

¹ Accuracy depends on the number of satellites used, SBAS data quality, multipath effects, device position/posture and other environmental conditions.
² Using SBAS (WAAS, EGNOS, MSAS). Not compatible with Topcon beacon receivers.

For more specification information:
topconpositioning.com/fc336

PRIMARY FEATURES

FC-336

Fully rugged, high performance, feature and capacity rich handheld with large storage capacity and long battery life.

Rugged and Compact



Topcon's FC-336 is a fully rugged handheld built to meet MIL-STD-810G with high-speed 3.5G WWAN wireless networking, designed for dependability

under the most extreme weather conditions, environments, and everyday use.

Long Life Battery

The field-swappable 5600mAh Li-ion battery with long battery life can be removed and replaced on the job site. An external battery charger is available as an optional accessory.

Easy, Intuitive Operation



Windows Mobile® 6.5 operating system and a 3.5" sunlight readable touch screen display provide quick, easy, and intuitive operation.

Integrated Sensors

Embedded 48 channel all-in-view tracking SIRF Star IV™ chipset provides position information by point positioning or by DGPS using SBAS corrections. The FC-336 incorporates a 5MP autofocus camera, electronic compass and an altimeter for GIS data collection applications.

Topcon TotalCare

This online resource comes with real live people ready to help. Get expert training from Topcon University's large collection of online materials, and expert help directly from Topcon Technical Support.

Access software and firmware updates, current publications, and guidance from the experts at Topcon all right from your computer or mobile device.

Please visit the TotalCare website to learn more.
topcontotalcare.com



7400 National Drive • Livermore • CA 94550
(925) 245-8300

Specifications subject to change without notice. ©2013 Topcon Corporation All rights reserved. P/N: 7010-2142 Rev. A TF Printed in U.S.A. 9/13

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license. Other trademarks and trade names are those of their respective owners.

KIT COMPONENTS



Standard Configuration

- FC-336 field controller
- Stylus pen
- Touch panel protective film
- USB cable
- Rechargeable battery
- Charger and power plug
- Manual and quick guide

Optional Accessories

- Pole bracket
- Rechargeable battery
- External GPS antenna
- Vehicle charger
- Office docking

Your local Authorized Topcon dealer is: